



# MTM5000 SERIES BENEFITS

## EXTENDED OPERATIONAL RANGE

- Up to 10W transmit power (MTM5400/5500) and with class leading receiver sensitivity delivers comprehensive network coverage
- Integrated DMO Gateway, DMO Repeater capabilities (MTM5400/5500), ensure secure and resilient communications where needed most

## SUPERIOR AUDIO PERFORMANCE

- Enhanced audio architecture delivering the loudest and clearest audio performance of any Motorola TETRA mobile available on the market<sup>1</sup>

## HIGH SPEED DATA CONNECTIVITY

- TEDS Ready hardware - with a simple software license upgrade, enables 20x faster data connectivity for accessing back-office systems and databases
- Integrated USB 2.0 PEI, enabling rapid radio programming and standardised interfacing to data terminals and accessories. For additional flexibility, USB host and slave modes are also supported

## LOW USER MIGRATION COSTS

- Familiar cellular style user interface and high resolution colour display for enhanced usability and reduced staff training costs
- Same intuitive user interface as latest MTP3000 Series and MTP6000 Series TETRA portable radios
- Re-use of common accessories using GCAI connector

## ENHANCED END TO END ENCRYPTION OPTIONS

- Integrated hardware for SIM based end to end encryption
- Universal Crypto Module option<sup>2</sup>

## LOCATION SERVICES

- The MTM5000 Series supports Global Navigation Satellite Systems (GNSS) based location services for GPS, GLONASS and BeiDou, as well as Satellite Based Augmentation Systems (SBAS) including WASS, EGNOS, MSASA, GAGAN and QZSS (Japan)

## ADVANCED TERMINAL MANAGEMENT

- USB 2.0 interface for fast radio programming via Motorola Solutions Integrated Terminal Management (ITM) solution

## FLEXIBLE INSTALLATION OPTIONS

- Fully DIN compatible and available in Dash, Desk, Remote Head and Motorcycle mount formats
- Supports multiple control heads - an ideal solution for installations in trains, ambulances and fire vehicles where more than one control point might be required
- Supports multiple transceivers - an ideal solution for multiple agency, joint operations, or multi-task communications including bilateral such as cross-border operations
- MTM5500 ethernet style connections enable up to 40m separation to either the new ReCH Control Head or the TSCH (IP55)
- Other Equipment Manufacturer (OEM) control head solutions can be developed using the Remote Display Control (RDC) protocols

## RUGGED DESIGN WITH EXCEPTIONAL RELIABILITY

- Includes IP67 control head option, for exposed and challenging environments
- Front and Rear rugged GCAI connector for reliable connection of audio and data peripheral equipment
- Mobile radio and accessories are performance matched for enhanced reliability



# MTM5000 SERIES SPECIFICATIONS



## MODELS - COMPLIANT WITH DIN 75490 (ISO 7736)

	MTM5400	MTM5500
Dash	Compact radio for fast vehicle installation	N.A.
Desk	Compact radio, for use in the office. Optional range of accessories such as desk tray with integrated loudspeaker	N.A.
Multiple Remote Control Head	N.A.	Radio with multiple remote mount control head capability
	N.A.	Range of installation options enable use in cars, vans and other vehicles
Multiple Transceiver or Control Head	N.A.	Range of installation options enable use in cars, vans and other vehicles
Motorcycle	Environmentally enhanced radio meeting IP67 specification. Suitable for demanding environments such as motorcycle, fire appliance and marine installations	N.A.
Expansion head "Databox"	Radio without a control head, for data applications, or customised application development	

## GENERAL

	Dimensions HxWxD (mm)	Weight Typical (g)	Dimensions HxWxD (mm)	Weight Typical (g)
Dash and Desk models (transceiver + control head)	60x188x198	1300	N.A.	N.A.
Transceiver only	45x170x169	1070	45x170x169	1070
Standard control head	60x188x31	230	N.A.	N.A.
Remote control head	60x188x39	300	60x188x39	300
Motorcycle control head	60x188x39	320	N.A.	N.A.

## USER INTERFACE & DISPLAY

Display	Diagonal dimension	2.8"
	Type	640x480 pixels, 65,000 colours
	Backlight	Variable backlight, User configurable
	Font sizes	Standard & Zoom mode (90 pixels, 4.5mm high) characters
TSCH		N.A. Available as option
Buttons & Keypad	Numeric	Integral backlit numeric keypad of 12 keys, with keypad lock option
	International keypad versions <sup>3</sup>	Roman, Arabic, Cyrillic, Korean, Chinese, Taiwanese characters
	Programmable function keys	3 programmable function keys (plus 10 programmable numeric keys)
	Navigation	4-way navigation key, menu and soft keys
Emergency		Emergency button with backlight
	Shortcuts	User configurable shortcuts to menus and common features using "One-Touch-Button" feature
Rotary	Dual Function	Talkgroup and volume change with lock option
Indication	LED	Tri-colour LED
	Tones	Configurable notification tones
User Interface Languages	Standard Options	Arabic, Chinese Simplified, Chinese Traditional, Croatian, Danish, Dutch, English, French, German, Greek, Hebrew, Hungarian, Italian, Korean, Lithuanian, Macedonian, Mongolian, Norwegian, Portuguese, Russian, Spanish, Swedish
	User defined	User programmable, using ISO 8859-1 character
Menu		Tailored to user needs
		Menu Shortcuts
		Menu Configuration
Contacts Management		Cellular Type
Contact List		Up to 1000 contacts
Multiple Dialling Methods		Up to 6 numbers per contact, Max 2000 numbers
Fast/Flexible Call Response		User selects how to dial
Multiple Ring Tones		Private Call Response to a Group Call via One Touch Button
Message Manager		Configurable with CPS
Text message list		Cellular Type
Intelligent Keypad Text Input		20
Status list		All Control Heads
Country/Network Code List		400
Scan lists		100
Discrete Mode		40 lists of 20 groups
Screen Saver		All Control Heads
Universal Time Display		gif image & text (any user's selection)
Keypad Lock		All Control Heads
Talkgroup Folders		All Control Heads
		Dual layer folder structure (folder/subfolder)
Favourite Folders		256 folders
		Up to 3 (to store any favourite talkgroup)

# MTM5000 SERIES SPECIFICATIONS

## ENVIRONMENTAL SPECIFICATIONS

Operating Temperature (°C)		-30 to +60
Storage Temperature (°C)		-40 to +85
Not in use - Storage	ETSI 300 019-1-1 CLASS 1.3	Non-Weather Protected Storage Locations
Not in use - Transportation	ETSI 300 019-1-2 CLASS 2.3	Public Transportation
Stationary use - Weather Protected Locations	ETSI 300 019-1-3 CLASS 3.2	Partly Temperature Controlled Locations
Mobile use - Ground Vehicle Installation	ETSI 300 019-1-5 CLASS 5.2	Climatic Tests
Mobile use - Ground Vehicle Installation	ETSI 300 019-1-5 CLASS 5M3	Mechanical Tests
Rail Certification Environmental	EN50155:2007 and IEC60571 ED.3.0	Environmental
MIL STD	810 C/D/E/F/G Specifications	All 11 categories met (or exceeded)
Dust and Water Ingress Protection	IP54 (dust cat. 2) IP67	Dash/Desk/Remote models Motorcycle model (only control head is IP67; transceiver is IP54)
		MTM5500 TSCH IP55

## ELECTRICAL SPECIFICATIONS

		MTM5400	MTM5500
Voltage Range		10.8 to 15.6 V DC	
Current Consumption (A, typ.)	Idle / Rx / Tx @ 10W	0.5 / 1.0 / 1.2 ( TX 3.4A Peak)	
	Idle / Rx / Tx @ 3W	0.5 / 1.0 / .9 (TX 2.2A Peak)	
	Tx - Multi Slot PD (4 slots) @ 5.6W	2.7	
	Tx - TEDS @ 3W	2.3	
	Using USB host	Adds 0.5A	

## RF SPECIFICATIONS

Frequency Bands (MHz)		350 - 390, 380 - 430, 410 - 470, 806 - 870
Transmitter RF Power	TETRA Release 1 TETRA Release 2 (TEDS)	10W, (Class 2) and 3W, (Class 3) 3W, (Class 3)
RF Power Control	6 Power Step Levels (steps of 5 dBm)	Starting at 15 dBm; finishing at 40 dBm
Receiver Class		A & B
Receiver Static Sensitivity (dBm)		-114 minimum, -116 typical (ETSI 300-392-2)
Receiver Dynamic Sensitivity (dBm)		-105 minimum, -107 typical (ETSI 300-392-2)

## GNSS SPECIFICATIONS

Simultaneous Satellite Systems		GPS plus one other GNSS, eg GLONASS, BeiDou
Mode of Operation		Concurrent tracking, SBAS capable, 72 channel
GNSS Antenna		Supports active antenna (5V, 25mA supply)
Tracking Sensitivity		2 meter (50% probable) @-130dBm
Accuracy		2m (50% probable) @-130dBm
Location Protocols		ETSI Location Information Protocol (LIP) Motorola LRRP

## VOICE SERVICES

Talkgroups		10,000 TMO, 2000 DMO
Phone book entries		1000 persons. Up to 6 numbers per entry (mobile, office etc). Max 2000 entries
Scan lists		40 lists of 20 talkgroups
Trunked Mode (TMO) Services	Group call	Late Entry, TMO/DMO Mapping
	Private call	Half / Full Duplex
	Telephony (PABX, PSTN, MS-ISDN)	Full Duplex
	DGNA	Up to 10,000 groups
Direct Mode (DMO) Services	Scanning	Attachment signalling, supports SWMI initiated attachment/detachment
		Group call Private call
Emergency (tailored by users)	Tactical	Emergency Group Call to ATTACHED talkgroup
	Non-Tactical	Emergency Group Call to DEDICATED talkgroup
	Individual	Emergency Call to PREDEFINED party (half/full duplex)
	Smart emergency	TMO/DMO/DMO to TMO automatic switching options
	Hot Mic	Configurable timers for automatic open mic (talk without PTT)
	Location	Location (GPS) sent with emergency
	Target Address	Sent to individual or group address (selected or dedicated)
Alarm (status message)	Emergency Status (or other pre-defined status)	

## DATA SERVICES

Status	Alias messages	400 Entries
	Options	Can be sent via One-Touch or via menu
Short Data Service (SDS)	Inbox/Outbox	Up to 200 Entries (short messages) At least 20 Entries for Outbox (long messages) <sup>†</sup> At least 10 Entries for Inbox (long messages) <sup>†</sup>
	Predictive Text	Cellular style iTAP predictive text entry
	Target Address	Sent to individual or group address (selected or dedicated)
	Voice Call Interaction	SDS messages can be sent and received during a voice call
Packet Data (PD)	Multi-slot PD	Data transmission with up to 4 slots supporting up to 28.8 kbit/s gross
	TETRA Enhanced Data Service (TEDS) (via software upgrade)	Supporting 25kHz and 50kHz channel bandwidths and enabling practical data rates of up to 80kbit/s
TEDS (capable)		QAM Channels: 25 kHz and 50 kHz (but not D8PSK channels)
		QAM modulation/coding modes: 4-QAM R1/2, 16-QAM R1/2, 64-QAM R1/2, and 64-QAM R2/3
WAP	Integrated WAP browser (including WAP-PUSH)	Integrated Openwave browser
		WAP 1.2.x and WAP 2.0 compatibility for UDP/IP Stack AT Commands - Full Set ETSI Mandatory Compliant
Peripheral Equipment Interface (PEI)	Interface Protocol	AT Multiplexer - 4 Virtual Physical Port (simultaneous PD, SDS, AT commands and Air Tracer SESSIONS) TNP1; enables simultaneous PD and SDS sessions
Terminal Management		Programmable via Motorola Integrated Terminal Management (iTM) solution

# MTM5000 SERIES SPECIFICATIONS

## GATEWAY SERVICES

	MTM5400	MTM5500
DMO/TMO Gateway		Group voice calls from DMO to TMO
		Group voice calls from TMO to DMO
		Emergency group call from DMO to TMO
		Emergency group call from TMO to DMO
		Call Pre-emption (in either direction)
		SDS messaging through the gateway from DMO to TMO or TMO to DMO
		Configurable routing of SDS messages to console or PEI <sup>2</sup>
		Point-to-point calls and SDS messages whilst operating as a Gateway

## REPEATER SERVICES

DMO Repeater		Repeats DMO voice calls on selected talkgroup
		Repeats SDS and Status messaging on selected talkgroup
		ETSI type 1A DMO Repeater for channel efficient operation
		Transmission of Repeater Presence Signal
		Priority Call
		Emergency Call (Pre-emptive Priority Call)
		E2EE Encrypted DMO traffic
		Monitoring of and participation in calls whilst in Repeater mode
	Configurable Repeater Power Levels	

## INTERFACES

RS232		Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT
USB		USB 2.0 support for PEI (Two Virtual Ports via standard Windows drivers enable PC applications to run simultaneously Packet Data and AT Commands)
		USB 2.0 support for PEI (Four Virtual Ports via AT Multiplexer enable PC applications to run simultaneously Packet Data, AT Commands, SDS, SCOUT); rapid programming
		USB On-The-Go (host & slave) capability for intelligent PEI applications
Rugged Accessory Connector (GCAI)		GCAI - Motorola accessory and ancillary interface for connection of accessories, data terminals and programming
General Purpose Input/Output	Digital I/O	7 (4 on remote and motorcycle control head, 3 on transceiver)
	Analog input	4 (1 on remote and motorcycle control head, with 4 levels)

## SECURITY FEATURES

Air Interface Encryption	Algorithms	TEA1, TEA2, TEA3
	Security Classes	Class 1 (Clear), Class 2 (SCK), Class 3G
	Authentication	Infrastructure initiated and made mutual by terminal
Provisioning		Secure provisioning tool via Key Variable Loader (KVL)
User Access Control		PIN/PUK code access
	Service Profile Selection for Radio User Assignment / Radio User Identity (RUA/RUI) Operation	Based on login credentials, a radio user can be limited to only those radio capabilities defined in pre-installed service profiles, selected by the infrastructure
Data		Packet Data user authentication
End to End Encryption (E2EE)	Voice E2EE	Enhanced End to End Encryption with OTAR supported through Universal Crypto Module (UCM) and SIM (via integrated card slot) and or Crypt 2 Broadband IP unit.
	Packet Data E2EE	
	Short Data (SDS) E2EE	

## REGULATORY COMPLIANCE

Radio (RED Article 3.2)	EN 302 561
EMC (R&TTE Article 3.1.b)	EN 301 489-1
	EN 301 489-18
Electrical Safety (R&TTE Article 3.1.a)	EN 60950-1
	EN50360 EME
Environmental	WEEE Directive
	EN50155 (IEC 60571 ED. 3.0)
Automotive	E-mark, ECE Regulation No.10 for Electrical/Electronic-Subassembly
Rail Certification EMC	EN50121-3-2 (IEC 62236-3-2 Ed.2.0)

For more information, please visit: [motorolasolutions.com/MTM5000](https://motorolasolutions.com/MTM5000)

<sup>1</sup>Assuming the appropriate audio accessory is used

<sup>2</sup>Model specific

<sup>3</sup>For availability of other language keypads please contact your local Motorola Solutions representative

<sup>4</sup>Long messages of up to 1,000 characters

<sup>5</sup>Future software release

Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, UK.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2020 Motorola Solutions, Inc. All rights reserved. (01-20)