# **WAVE PTX<sup>®</sup> RADIO TLK 150** RAPID, RELIABLE DEPLOYMENT.

# EASY TO USE AND MANAGE BUILT FOR THE JOB - SAFELY OPERATE IN VEHICLE EUROPE-WIDE<sup>\*</sup> PUSH-TO-TALK

+

Vol

Li

.dl 🕾 Z 🛠 ♀

1 Dispatch

**部のK (P1 P2) 5余** 

Get your team up and running quickly. Combine the broad coverage of a Europe-wide broadband network\* with the ease of push-to-talk radio communications.

**USE EUROPE-WIDE**<sup>\*</sup>.

Safely operate while driving with one button push-to-talk. Manage talk groups and subscriptions in real time. Increase coverage, connections, and productivity without expanding infrastructure.

There's no costly or time-consuming spectrum licensing, or manual programming required.

## **FEATURE HIGHLIGHTS**

▲CH▶

MOTOROLA

- Private and group push-to-talk
- Over-the-air device management
- 4G LTE, 3G and Wi-Fi connectivity
- GPS location tracking
- Loud and clear audio
- Real-time presence
- Bluetooth® enabled
- 12V/24V dual voltage support



#### **GENERAL SPECIFICATIONS**


Network	4G LTE: 1,2,3,4,5,7,8,13,17,19,20,21,28
Network	3G UMTS: 1,2,5,8
Channel Capacity	96 Channels
Contact List	300 contacts
Dimensions (W x H x L)	169mm x 44mm x 93mm
Weight	640 g
Voice Codec	OPUS
Wi-Fi	802.11 a/b/g/n - 2.4 / 5.0 GHz
Bluetooth	Bluetooth V4.2 BR/EDR + BLE
Location	GNSS / A-GPS (GPS, GLONASS, Galileo, BeiDou)
IP Rating	IP54 IEC60529
Apps Supported	Powered by WAVE PTX
Encryption	AES-256
Antennas	LTE antennas - External GNSS antenna - External Wi-Fi/Bluetooth antenna - Internal
Connectors	Front RJ45 connector for wired mobile microphone Back antenna SMA connectors Back 20-pin MAP connector for other accessories
Rated Audio	4 W (Internal) 16 W (External - 4 ohms)
Audio Distortion @ Rated Audio	3% (Typical)

ENVIRONMENTAL SPECIFICATIONS		
Operating Temperature	-20°C to +60°C	
Storage Temperature	-40°C to +85°C	
Thermal Shock	Per MIL STD-810	
Humidity	Per MIL STD-810	
ESD	IEC61000 - 4-2 Level 4	
Dust and Water Intrusion	IEC60529 - IP54 Cat 2	
Packaging Test	Per MIL STD-810	

MIL 810G STANDARD**	METHOD	PROCEDURES
Low Pressure	500.5	,
High Temperature	501.5	,
Low Temperature	502.5	,
Temperature Shock	503.5	,
Solar Radiation	505.5	I-C
Rain Blowing	506.5	
Dust Blowing	510.5	
Immersion	512.5	
Vibration	514.6	
Shock	516.6	I,IV

\*\*Also meets equivalent MIL-STD-810-C, -D, -E and -F





## **TLK 150 ACCESSORIES**



#### PUSH-TO-TALK SOLUTIONS

Make communicating easier and safer with these optional accessories from a simple  $\mathsf{PTT}$  microphone to a complete hands free solution.

PMMN4129	Wideband Compact Mobile Microphone
GMMN4065	Visor Microphone
RLN4856	Footswitch Push-to-Talk
RLN4857	Remote Mount Pushbutton Push-to-Talk
RLN4836	Emergency Footswitch
PMMN4127	WM500 Bluetooth Remote Speaker Microphone



#### **EXTERNAL SPEAKER**

Boost audio	at your	workstation	or in	your vehicle.
				,

AC000240A01	Wideband External Speaker, 13 W
-------------	---------------------------------

ANTENNAS	
AN000359A01	GNSS Dash Mount Antenna
AN000358A01	LTE Dash/Glass Mount Antenna



MUUNTING ACCESSURIES	
Choose where to mount the radio without compromising safety.	
RLN6466	Low Profile Trunnion Kit
RLN6467	High Profile Trunnion Kit
RLN6468	Key Lock Trunnion Mount
FTN6083	In-Dash Mounting Kit - DIN
HLN9073	Microphone Hang-Up Clip (install by screwing to convenient surface)
HLN9414	Universal Microphone Hang-Up Clip (no installation required)

DESKTOP ACCESSORIES	
Mounting aids for use in desktop control stations.	
GLN7318	Desktop Tray Without Speaker
PMPN4076	Desktop Wedge Tray With Built-in Power Supply
A range of cables to connect the power supply and TLK 150 are available.	

Talk to your authorised Motorola Solutions reseller for more information.

CABLES AND ACCESSORIES		
HKN4137	DC Power Cable With Inline Fuse 3m/10ft, 15A	
HKN9327	Ignition Switch Cable	
HLN9457	16 Pin MAP Connector Kit	
HKN4192	Battery Power Cable (6m / 20ft, 20 A)	
GMKN4084	Speaker Extension Cable	

## YOUR PATH TO EUROPE-WIDE\* PTT PLACE YOUR ORDER. GET YOUR RADIO AND START TALKING



## WARRANTY AND REPAIRS

The TLK 150 radio includes 12 months cover for hardware manufacturing defects as standard, and you have access to software updates and Motorola Solutions technical support for the duration for your WAVE PTX subscription.

For additional peace of mind, we offer optional extended cover to provide hardware repair for three years.

### Learn more at www.motorolasolutions.com/WAVEPTX

\*Coverage limited to EU, EFTA and UK and will vary depending on conditions.

\*\*\*Configuration is carried out by reseller or reseller may give end user permissions to carry our configuration.

Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, United Kingdom.

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to change without notice. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. © 2020 Motorola Solutions, Inc. All rights reserved. (08/20)

